



TOPCO OILSITE PRODUCTS LTD.

THREAD COMPOUNDS

Sealants and Lubricants

THREAD COMPOUND TECHNICAL DATA

SRL SUCKER ROD LUBRICANT



- SRL is an environmentally safe, specialty lubricant developed for the consistent control of torque during the makeup of sucker rod connections.

This product contains inhibitors that prevent the pitting damage caused by H₂S and ensure maximum corrosion protection of both pin and box threads.

SRL is packaged in convenient polyethylene squeeze top bottles. The flip-top dispensing lid allows ease of application of a single bead of lubricant on the pin threads.

■ Service Recommendations

API sucker rod connections

■ Packaging

1 L Plastic Net Weight 0.9 Kg (2 lb) Packaged 12 Bottles Per Case

Refer to Manufacturer's Material Safety Data Sheet for Precautionary and Handling Information

LOCATIONS

Calgary Office
Bay 7, 3401 - 19 Street N.E.
Calgary, AB T2E 6S8
Phone: 403/219-0255
Fax: 403/291-3042

Clairmont Office
9402 - 99 Street
Clairmont, AB T0H 0W0
Phone: 780/567-2398
Fax: 780/567-2413

Red Deer Distribution Centre
7932 Edgar Industrial Way
Red Deer, AB T4P 3R2
Phone: 403/341-4417
Fax: 403/346-5122

Redcliff Office
114 Elbow Drive N.E.
Redcliff, AB T0J 2P0
Phone: 403/526-3321
Fax: 403/526-8036

Edmonton Distribution Centre
9519 - 28 Avenue
Edmonton, AB T6N 0A3
Phone: 780/436-3400
Fax: 780/436-3659

Oklahoma City Distribution Centre
8200 West Reno
Oklahoma City, OK USA 73127
Phone: 405/491-8521
Fax: 405/491-8521



TOLL FREE: 1-800-222-6449

www.topcoilsite.com