



TK II MODIFIED®



TK II is a synthetic based thermal compound developed for use in geo-thermal and steam injection services. This product provides a leak-proof seal in both API and premium connections in high temperatures and pressures. The metallics used in the formulation prevent thread galling and seizure. The chemical inhibitors minimize the effects of corrosive environments.

Service Recommendations

API casing and tubing

Product Specifications

Service Rating	345°C/650°F
Drop Point	400°C/752°F
Brushability	-18°C /0°F

Packaging

4.5 L	Net 10 lb
10 L Steel	Net 30 lb
20 L Steel	Net 50 lb
170 L Steel	Net 480 lb

Refer to Manufacturer's Material Safety Data Sheet for Precautionary and Handling Information

LOCATIONS

Calgary Office
 Bay 7, 3401 - 19 Street N.E.
 Calgary, AB T2E 6S8
 Phone: 403/219-0255
 Fax: 403/291-3042

Clairmont Office
 9402 - 99 Street
 Clairmont, AB T0H0W0
 Phone: 780/567-2398
 Fax: 780/567-2413

Red Deer Distribution Centre
 7932 Edgar Industrial Way
 Red Deer, AB T4P 3R2
 Phone: 403/341-4417
 Fax: 403/346-5122

Redcliff Office
 114 Elbow Drive N.E.
 Redcliff, AB T0J 2P0
 Phone: 403/526-3321
 Fax: 403/526-8036

Edmonton Distribution Centre
 9519 - 28 Avenue
 Edmonton, AB T6N 0A3
 Phone: 780/436-3400
 Fax: 780/436-3659

Oklahoma City
 Distribution Centre
 8200 West Reno
 Oklahoma City, OK
 USA 73127
 Phone: 405/491-8521
 Fax: 405/491-8521

TOLLFREE: 1-800-222-6449



www.topcooilsite.com