



**TOPCO** OILSITE PRODUCTS LTD.  
**THREAD COMPOUNDS**  
*Sealants and Lubricants*

## THREAD COMPOUND TECHNICAL DATA

# ZINCOTE®



- Zincote is the API formulated tool joint compound (Bulletin 7A1) that contains a 50% loading of metallic zinc to prevent galling of rotary shouldered connections in high torque applications.

The formulation is made using a premium base grease and has additives to prevent corrosion and maximize compound adhesion during cold, wet drilling conditions.

### Service Recommendations

Tool joints and drill collars

### Product Specifications

Specific Gravity	2.41g / cc
Service Rating	200°C / 392°F
Drop Point	240°C / 464°F
Brushability	-18°C / 0°F

### Packaging

10 L STEEL / 2.5 gal.	Net 15.9 kg	Net 35 lb
16 L PLASTIC / 4.0 gal.	Net 24.9 kg	Net 55 lb

Refer to Manufacturer's Material Safety Data Sheet for Precautionary and Handling Information

LOCATIONS

**Calgary Office**  
 Bay 7, 3401-19 Street N.E.  
 Calgary, AB T2E 6S8  
 Phone: 403/219-0255  
 Fax: 403/291-3042

**Clairmont Office**  
 9402 - 99 Street  
 Clairmont, AB T0H0W0  
 Phone: 780/567-2398  
 Fax: 780/567-2413

**Red Deer Distribution Centre**  
 7932 Edgar Industrial Way  
 Red Deer, AB T4P 3R2  
 Phone: 403/341-4417  
 Fax: 403/346-5122

**Redcliff Office**  
 114 Elbow Drive N.E.  
 Redcliff, AB T0J 2P0  
 Phone: 403/526-3321  
 Fax: 403/526-8036

**Edmonton Distribution Centre**  
 9519 - 28 Avenue  
 Edmonton, AB T6N 0A3  
 Phone: 780/436-3400  
 Fax: 780/436-3659

**Oklahoma City Distribution Centre**  
 8200 West Reno  
 Oklahoma City, OK USA 73127  
 Phone: 405/491-8521  
 Fax: 405/491-8521



**TOLLFREE: 1-800-222-6449**

**www.topcoilsite.com**