



Combination Sleeve-Type Sucker Rod Socket

DESCRIPTION	PART NUMBER	
	2"	2½"
Socket, Complete		
Outside Diameter	1 29/32"	1 5/16"
Components:		
① Bowl, Lower	552-529-000	552-531-500
② Bowl, Upper	552-529-300	552-531-600
③ Guide, Spring, Lower	552-705-000	
④ Guide, Spring, Upper	552-705-400	552-705-100
⑤ Ring, Control	552-529-200	552-525-100
⑥ *Slips, Rod		
5/8" and 3/4" Rods	552-527-800	552-530-000
3/4" and 7/8" Rods	552-527-900	552-530-100
⑦ *Slip Unit, Single End		
1 5/8" Coupling	552-528-100	
1 3/16" Coupling		552-531-400
⑧ Spring, Lower	552-521-200	552-522-300
⑨ Spring, upper	552-529-400	552-531-700
Top (With 3/4" API pin)	552-528-900	552-522-000
Accessories:		
⑪ Slips, Rod		
1/2" and 5/8" Rods	552-526-200	
5/8" and 3/4" Rods		552-530-000
3/4" and 7/8" Rods	552-527-900	
7/8" and 1" Rods		552-530-200
Slip Unit, Reversible		
1 3/8" and 1 5/8"		
Slip Unit, Single End		
1 3/8" Coupling	552-528-510	
1 1/2" Coupling		552-531-410
1 1/16" Coupling	552-528-120	
1 5/8" Coupling		552-531-300
1 11/16" Coupling		552-531-310

The Trico Combination Sleeve-Type Sucker Rod Socket is used for fishing rod breaks and sucker rod couplings. The socket has an upper bowl fitted with rod slips suitable for catching two sizes of rods, and a lower bowl fitted with a single end slip unit designed to engage and catch one size sucker rod coupling.

