



GREEN SEAL II THERMAL



Green-Seal II Thermal is a premium thermal compound formulated for use on casing and tubing used in high temperature steam injection services.

This environmentally friendly product is free of all heavy metals. It is blended using synthetic base materials and has a proprietary loading of inorganic additives to protect against extreme wear. Anti-corrosion inhibitors ensure that tubulars may be stored for extended periods of time without concern for pitting of the threads.

The premium quality greases allow for ease of application of Green Seal II Thermal in all types of weather conditions.

Green Seal II Thermal has a coefficient of friction that is similar to that of API Modified. This characteristic allows the compound to be run at standard pipe torques as recommended by the manufacturer.

Product Specifications

| | |
|----------------|----------------|
| Service Rating | 371°C / 700°F |
| Drop Point | 386°C / 727° F |
| Brushability | -18 °C / 0° F |

Service Recommendations

API casing, tubing, and premium threaded connections

Packaging

| | | |
|------------|-------------|-----------|
| 10 L Metal | Net 13.6 kg | Net 30 lb |
| 20 L Metal | Net 22.7 kg | Net 50 lb |

Refer to Manufacturer's Material Safety Data Sheet for Precautionary and Handling Information

LOCATIONS

Calgary Office
 Bay 7, 3401 - 19 Street N.E.
 Calgary, AB T2E 6S8
 Phone: 403/219-0255
 Fax: 403/291-3042

Clairmont Office
 9402 - 99 Street
 Clairmont, AB T0H 0W0
 Phone: 780/567-2398
 Fax: 780/567-2413

Red Deer Distribution Centre
 7932 Edgar Industrial Way
 Red Deer, AB T4P 3R2
 Phone: 403/341-4417
 Fax: 403/346-5122

Redcliff Office
 114 Elbow Drive N.E.
 Redcliff, AB T0J 2P0
 Phone: 403/526-3321
 Fax: 403/526-8036

Edmonton Distribution Centre
 9519 - 28 Avenue
 Edmonton, AB T6N 0A3
 Phone: 780/436-3400
 Fax: 780/436-3659

Oklahoma City Distribution Centre
 8200 West Reno
 Oklahoma City, OK
 USA 73127
 Phone: 405/491-8521
 Fax: 405/491-8521

TOLL FREE: 1-800-222-6449



www.topcoilsite.com