

# SRL (Sucker Rod Lubricant)



Topco's SRL was formulated as a specialty lubricant to provide for the consistent control of torque during the make-up of sucker rod threads. For many years there was not a recommended product for sucker rod threads and field operations used diesel, API Modified compound or ran dry during installation of the sucker rods in a well.

SRL has a heavy loading of corrosion inhibitors to prevent thread pitting damage caused by well fluids, H<sub>2</sub>S, or having rods being stored in an outdoors environment.

SRL was developed for field operations and is packaged in polyethylene squeeze top bottles for convenience of application and to avoid wasting of the product. This lubricant is also used by a number of manufacturers as their standard inhibitor for storage and transport of sucker rods to the field.

## ▶ SERVICE RECOMMENDATIONS

Blended for use as a lubricant ONLY for sucker rods threads.

## ▶ PERFORMANCE CHARACTERISTICS

- A lubricant without any solid additives
- Has a high temperature base grease with anti-corrosion additives
- Tested in both outdoor storage conditions and a salt fog cabinet (ASTM)
- Provides a minimum of 2 years of corrosion resistance

## ▶ PRODUCT SPECIFICATIONS

Thickener	Calcium Complex
Fluid Type	Petroleum
Flash Point	> 180°C / 356°F
Service Rating	N/A
NLGI Grade	00
Color	Amber
Friction Factor	N/A
Pen Range	400 – 430 (ASTM D217)
Brushability	N/A
Drop Point	> 204°C / 400°F

## ▶ PACKAGING

1 l Polyethylene Flip Top Bottle	Net 0.9 kg / 2 lb (12 per case)
20 l steel / 5.0 gallon	Net 18 kg / 40 lb
205 l drum / 55 gallon	Net 181 kg / 400 lb

**Note:** The torque correction factor is influenced by a variety of conditions such as pipe size, thread geometry, drilling mud contaminants, and drilling environment. In all applications experience and prior knowledge should be used to adjust make-up torques as the torque correction number provided is relative.

**Warranty:** This compound shall be free of defects at time of manufacture. Warranty shall be limited to the refund of the purchase price. All other liability is negated and disclaimed and Topco Oilsite Products shall not be liable for consequential or incidental damages.



[www.topcooilsite.com](http://www.topcooilsite.com)

toll free: 1-800-222-6448



**TOPCO** OILSITE PRODUCTS LTD.



**TOPCO** OILSITE PRODUCTS USA, INC.