

Thermal-Kote



Thermal-Kote was developed for use on tubing in steam injection and SAG-D applications.

▶ SERVICE RECOMMENDATIONS

Thermal-Kote may be used on any API tubing connections with EUE, 8 round, or buttress style threads.

▶ PERFORMANCE CHARACTERISTICS

- A high temperature thermally stable product recommended for use in steam injection service
- Blended with extreme pressure additives and corrosion inhibitors for maximum thread protection
- Not recommended for casing in long term thermal applications

▶ PRODUCT SPECIFICATIONS

Thickener	Calcium Sulfonate Complex
Fluid Type	Petroleum / Partial Synthetic
Flash Point	> 280°C / 536°F
Service Rating	300°C / 572°F
NLGI Grade	1
Color	Copper
Pen Range	300 – 360 (ASTM D217) seasonal adjustment
Brushability	-18°C / 0°F
Drop Point	> 310°C / 590°F

▶ PACKAGING

500 ml Brush Top Can	Net 454 gm / 1 lb
4.5 l steel / 1.0 gallon	Net 4.5 kg / 10 lb

Note: The torque correction factor is influenced by a variety of conditions such as pipe size, thread geometry, drilling mud contaminants, and drilling environment. In all applications experience and prior knowledge should be used to adjust make-up torques as the torque correction number provided is relative.

Warranty: This compound shall be free of defects at time of manufacture. Warranty shall be limited to the refund of the purchase price. All other liability is negated and disclaimed and Topco Oilsite Products shall not be liable for consequential or incidental damages.



www.topcoilsite.com
toll free: 1-800-222-6448

