

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name • 65% Zincote®
Synonyms • Anti-Seize; Lubricant; Sealant; Thread Compound

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s) • Anti-Seize, Lubricant, Sealant, lubricate & seal tool joint threads

1.3 Details of the supplier of the safety data sheet

Manufacturer • Topco Oilsite Products Ltd.
Bay 7, 3401 - 19th Street N.E.
Calgary, Alberta T2E 6S8
Canada
www.topcoilsite.com
msds@topcoilsite.com

Telephone (General) • 403-219-0255

1.4 Emergency telephone number

Manufacturer • 403-219-0255
Poison & Drug Information Service (Alberta Health Services) • 1-800-332-1414

Section 2: Hazards Identification

EU/EEC

According to: Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 2015/830]

2.1 Classification of the substance or mixture

CLP • Carcinogenicity 2 - H351
Hazardous to the aquatic environment Acute 1 - H400
Hazardous to the aquatic environment Chronic 1 - H410

2.2 Label Elements

CLP

WARNING



Hazard statements • H351 - Suspected of causing cancer.
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements

Prevention • P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response • P308+P313 - IF exposed or concerned: Get medical advice/attention.
P391 - Collect spillage.

Storage/Disposal • P405 - Store locked up.
P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3 Other Hazards

CLP • Heating above the melting point releases metallic oxides which may cause metal fume fever by inhalation. The symptoms are shivering, fever, malaise and muscular pain.
According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

UN GHS Revision 4

According to: **UN Globally Harmonized System of Classification and Labelling of Chemicals (GHS): Fourth Revised Edition**

2.1 Classification of the substance or mixture

UN GHS • Skin Mild Irritation 3
Carcinogenicity 2
Hazardous to the aquatic environment Acute 1
Hazardous to the aquatic environment Chronic 1

2.2 Label elements

UN GHS

WARNING



Hazard statements • Causes mild skin irritation
Suspected of causing cancer.
Very toxic to aquatic life
Very toxic to aquatic life with long lasting effects

Precautionary statements

Prevention • Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection/face protection.

Response • If skin irritation occurs: Get medical advice/attention.
IF exposed or concerned: Get medical advice/attention.
Collect spillage.

Storage/Disposal • Store locked up.
Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3 Other hazards

UN GHS • Heating above the melting point releases metallic oxides which may cause metal fume fever by inhalation. The symptoms are shivering, fever, malaise and muscular pain
According to the Globally Harmonized System for Classification and Labeling (GHS) this product is considered hazardous

United States (US)

According to: **OSHA 29 CFR 1910.1200 HCS**

2.1 Classification of the substance or mixture

OSHA HCS 2012 • Carcinogenicity 2
Hazards Not Otherwise Classified - Health Hazards - Metal fume fever

2.2 Label elements

OSHA HCS 2012

WARNING



Hazard statements • Suspected of causing cancer.

Precautionary statements

Prevention • Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/protective clothing/eye protection/face protection.

Response • IF exposed or concerned: Get medical advice/attention.

Storage/Disposal • Store locked up.
Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3 Other hazards

OSHA HCS 2012 • Heating above the melting point releases metallic oxides which may cause metal fume fever by inhalation. The symptoms are shivering, fever, malaise and muscular pain. Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to: WHMIS 2015

2.1 Classification of the substance or mixture

WHMIS 2015 • Carcinogenicity 2
Health Hazards Not Otherwise Classified 1

2.2 Label elements

WHMIS 2015

DANGER



Hazard statements • Suspected of causing cancer.
Heating above the melting point releases metallic oxides which may cause metal fume fever by inhalation. The symptoms are shivering, fever, malaise and muscular pain

Precautionary statements

Prevention • Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/protective clothing/eye protection/face protection.

Response • IF exposed or concerned: Get medical advice/attention.

Storage/Disposal • Store locked up.

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3 Other hazards

WHMIS 2015

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

3.1 Substances

- Material does not meet the criteria of a substance.

3.2 Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Zinc powder, stabilized	CAS: 7440-66-6 EC Number: 231-175-3	50% TO 70%	NDA	EU CLP: Annex VI, Table 3.1: Aquatic Acute 1, H400; Aquatic Chronic 1, H410 UN GHS Revision 4: Skin Irrit. 3; Aquatic Acute 1; Aquatic Chronic 1 OSHA HCS 2012: Comb. Dust; Hazard Not Otherwise Classified - Health Hazard - Metal fume fever WHMIS 2015: Comb. Dust; Hazard Not Otherwise Classified - Health Hazard - Metal fume fever	NDA
Crystalline silica	CAS: 14808-60-7 EC Number: 238-878-4	0.5% TO 40.036%	NDA	EU CLP: Carc. 1A, H350i; STOT RE 1, H372 (Lungs, Inhl) UN GHS Revision 4: Carc. 1A; STOT RE 1 (Lungs, Inhl) OSHA HCS 2012: Carc. 1A; STOT RE 1 (Lungs, Inhl) WHMIS 2015: Carc. 1A; STOT RE 1 (Lungs, Inhl)	NDA
Asphalt	CAS: 8052-42-4 EINECS: 232-490-9	0% TO 39.286%	Ingestion/Oral-Rat LD50 • >5000 mg/kg	EU CLP: Carc. 2, H351 UN GHS Revision 4: Carc. 2 OSHA HCS 2012: Carc. 2 WHMIS 2015: Carc. 2	NDA
Talc	CAS: 14807-96-6 EC Number: 238-877-9	3% TO 15%	NDA	EU CLP: STOT RE 1, H372 (Lungs, Inhl) UN GHS Revision 4: Skin Irrit. 3; STOT RE 1 (Lungs, Inhl) OSHA HCS 2012: STOT RE 1 (Lungs, Inhl) WHMIS 2015: STOT RE 1 (Lungs, Inhl)	NDA
Chlorite	CAS: 1318-59-8 EINECS: 215-285-9	0.5% TO 4.5%	NDA	EU CLP: Not Classified UN GHS Revision 4: Not Classified OSHA HCS 2012: Not Classified WHMIS 2015: Not Classified	NDA
Dolomite	CAS: 16389-88-1 EINECS: 240-440-2	0.25% TO 1.5%	NDA	EU CLP: Not Classified UN GHS Revision 4: Not Classified OSHA HCS 2012: Not Classified WHMIS 2015: Not Classified	NDA
Carbonic acid, magnesium salt (1:1)	CAS: 546-93-0 EC Number: 208-915-9	0.05% TO 0.75%	Ingestion/Oral-Rat LD50 • 8000 mg/kg	EU CLP: Not Classified UN GHS Revision 4: Not Classified OSHA HCS 2012: Not Classified WHMIS 2015: Not Classified	NDA
Zinc O,O-bis(mixed iso-butyl and pentyl) phosphorodithioate	CAS: 68457-79-4	0.5355% TO 0.714%	NDA	EU CLP: Not Classified UN GHS Revision 4: Acute Tox. 5 (orl)	NDA

	EINECS:270-608-0			OSHA HCS 2012: Not Classified WHMIS 2015: Not Classified	
--	------------------	--	--	---	--

See Section 16 for full text of H-statements.

Section 4 - First Aid Measures

4.1 Description of first aid measures

- Inhalation** • Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing.
- Skin** • In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Get medical attention if symptoms occur.
- Eye** • In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. Get medical attention if symptoms occur.
- Ingestion** • Obtain medical attention immediately if ingested.

4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to Physician** • All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5 - Firefighting Measures

5.1 Extinguishing media

- Suitable Extinguishing Media** • In case of fire use media as appropriate for surrounding fire.
- Unsuitable Extinguishing Media** • No data available

5.2 Special hazards arising from the substance or mixture

- Unusual Fire and Explosion Hazards** • None
- Hazardous Combustion Products** • No data available

5.3 Advice for firefighters

- Structural firefighters' protective clothing will only provide limited protection. Wear positive pressure self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal Precautions** • Ventilate the area. Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact.
- Emergency Procedures** • Keep unauthorized personnel away. Stay upwind.

6.2 Environmental precautions

- Avoid run off to waterways and sewers.

6.3 Methods and material for containment and cleaning up

- Containment/Clean-up Measures** • Carefully shovel or sweep up spilled material and place in suitable container.

6.4 Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling • Use only with adequate ventilation. Use good safety and industrial hygiene practices. Wear appropriate personal protective equipment, avoid direct contact. Avoid contact with skin, eyes, and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

7.2 Conditions for safe storage, including any incompatibilities

Storage • Keep container tightly closed. Store in a cool, dry, well-ventilated place.

7.3 Specific end use(s)

- Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines						
	Result	ACGIH	Argentina	Australia	Canada Alberta	Canada British Columbia
Asphalt (8052-42-4)	TWAs	0.5 mg/m ³ TWA (fume, inhalable particulate matter, as benzene-soluble aerosol)	0.5 mg/m ³ TWA [CMP] (Bitumen, inhalable fraction, as soluble aerosol in benzene)	5 mg/m ³ TWA (fume)	5 mg/m ³ TWA (Petroleum; Bitumen, fume)	0.5 mg/m ³ TWA (inhalable fume, as Benzene-soluble aerosol)
Carbonic acid, magnesium salt (1:1) (546-93-0)	TWAs	Not established	Not established	10 mg/m ³ TWA (containing no asbestos and <1% crystalline silica, inhalable dust, listed under Magnesite)	Not established	10 mg/m ³ TWA (total dust); 3 mg/m ³ TWA (respirable fraction)
Crystalline silica (14808-60-7)	TWAs	0.025 mg/m ³ TWA (respirable particulate matter)	0.05 mg/m ³ TWA [CMP] (respirable fraction)	0.1 mg/m ³ TWA (respirable dust)	0.025 mg/m ³ TWA (respirable particulate)	0.025 mg/m ³ TWA (respirable)
Talc (14807-96-6)	TWAs	2 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	2 mg/m ³ TWA [CMP] (respirable fraction, particulate matter containing no asbestos and less than 1% crystalline silica)	2.5 mg/m ³ TWA (containing no asbestos fibers)	2 mg/m ³ TWA (respirable particulate)	2 mg/m ³ TWA (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate)
Exposure Limits/Guidelines (Con't.)						
	Result	Canada Manitoba	Canada New Brunswick	Canada Northwest Territories	Canada Nova Scotia	Canada Nunavut
Asphalt (8052-42-4)	TWAs	0.5 mg/m ³ TWA (fume, inhalable particulate matter, as Benzene soluble aerosol)	5 mg/m ³ TWA (petroleum fumes)	0.5 mg/m ³ TWA (Bitumen, fume, as Benzene soluble aerosol (inhalable fraction))	0.5 mg/m ³ TWA (fume, inhalable particulate matter, as Benzene soluble aerosol)	0.5 mg/m ³ TWA (Bitumen, fume, as Benzene soluble aerosol (inhalable fraction))
	STELs	Not established	Not established	1.5 mg/m ³ STEL (Bitumen, fume, as Benzene soluble aerosol (inhalable fraction))	Not established	1.5 mg/m ³ STEL (Bitumen, fume, as Benzene soluble aerosol (inhalable fraction))
Carbonic acid, magnesium salt (1:1) (546-93-0)	TWAs	Not established	10 mg/m ³ TWA (particulate matter containing no Asbestos and <1% Crystalline silica)	10 mg/m ³ TWA	Not established	10 mg/m ³ TWA
	STELs	Not established	Not established	20 mg/m ³ STEL	Not established	20 mg/m ³ STEL
Crystalline silica (14808-60-7)	TWAs	0.025 mg/m ³ TWA (respirable particulate matter)	0.1 mg/m ³ TWA (respirable fraction)	0.05 mg/m ³ TWA (respirable fraction, listed under Silica - crystalline)	0.025 mg/m ³ TWA (respirable particulate matter)	0.05 mg/m ³ TWA (respirable fraction, listed under Silica - crystalline)

Talc (14807-96-6)	TWAs	2 mg/m3 TWA (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter)	2 mg/m3 TWA (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction)	2 mg/m3 TWA (respirable fraction)	2 mg/m3 TWA (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter)	2 mg/m3 TWA (respirable fraction)
Exposure Limits/Guidelines (Con't.)						
	Result	Canada Ontario	Canada Quebec	Canada Saskatchewan	Canada Yukon	China
Asphalt (8052-42-4)	STELs	Not established	Not established	1.5 mg/m3 STEL (fume and inhalable fraction, as Benzene soluble aerosol)	10 mg/m3 STEL (fume)	12.5 mg/m3 STEL (fume, as Benzene soluble matter)
	TWAs	0.5 mg/m3 TWA (fume, inhalable, as Benzene-soluble aerosol)	5 mg/m3 TWAEV (fume)	0.5 mg/m3 TWA (fume and inhalable fraction, as Benzene soluble aerosol)	5 mg/m3 TWA (fume)	5 mg/m3 TWA (fume, as Benzene soluble matter)
Carbonic acid, magnesium salt (1:1) (546-93-0)	TWAs	Not established	10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, total dust)	Not established	Not established	Not established
Dolomite (16389-88-1)	STELs	Not established	Not established	Not established	Not established	16 mg/m3 STEL (total dust); 8 mg/m3 STEL (respirable dust)
	TWAs	Not established	Not established	Not established	Not established	8 mg/m3 TWA (total dust); 4 mg/m3 TWA (respirable dust)
Crystalline silica (14808-60-7)	STELs	Not established	Not established	Not established	Not established	2 mg/m3 STEL (containing 10 - 50% free SiO ₂ , total dust); 1.4 mg/m3 STEL (containing 50 - 80% free SiO ₂ , total dust); 1 mg/m3 STEL (containing >80% free SiO ₂ , total dust); 1.4 mg/m3 STEL (containing 10 - 50% free SiO ₂ , respirable dust); 0.6 mg/m3 STEL (containing 50 - 80% free SiO ₂ , respirable dust); 0.4 mg/m3 STEL (containing >80% free SiO ₂ , respirable dust)
	TWAs	0.10 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, crystalline)	0.1 mg/m3 TWAEV (respirable dust)	0.05 mg/m3 TWA (respirable fraction, listed under Silica - crystalline (Trydimite removed))	300 particle/mL TWA (listed under Silica - Quartz, crystalline)	0.7 mg/m3 TWA (containing 50 - 80% free SiO ₂ , total dust); 0.3 mg/m3 TWA (containing 50 - 80% free SiO ₂ , respirable dust); 1 mg/m3 TWA (containing 10 - 50% free SiO ₂ , total dust); 0.7 mg/m3 TWA (containing 10 - 50% free SiO ₂ , respirable dust); 0.5 mg/m3 TWA (containing >80% free SiO ₂ , total dust); 0.2 mg/m3 TWA (containing >80% free SiO ₂ , respirable dust)

Talc (14807-96-6)	STELs	Not established	Not established	Not established	Not established	6 mg/m3 STEL (free SiO2 <10%, total dust); 2 mg/m3 STEL (free SiO2 <10%, respirable dust)
	TWAs	2 mg/m3 TWA (containing no Asbestos and <1% Crystalline silica, respirable)	3 mg/m3 TWAEV (respirable dust)	2 mg/m3 TWA (respirable fraction)	20 mppcf TWA	3 mg/m3 TWA (free SiO2 <10%, total dust); 1 mg/m3 TWA (free SiO2 <10%, respirable dust)

Exposure Limits/Guidelines (Con't.)

	Result	France	Germany DFG	India	Indonesia	Israel
Asphalt (8052-42-4)	TWAs	Not established	Not established	Not established	0.5 mg/m3 TWA (soluble aerosol, fume)	0.5 mg/m3 TWA (fume, inhalable fraction, as benzene soluble aerosol)
Carbonic acid, magnesium salt (1:1) (546-93-0)	TWAs	10 mg/m3 TWA [VME]	Not established	Not established	10 mg/m3 TWA	Not established
Crystalline silica (14808-60-7)	TWAs	0.1 mg/m3 TWA [VME] (restrictive limit, alveolar fraction)	Not established	(10600)/(%Quartz + 10) mppcm TWA, dust count; (10)/(%Quartz + 2) mg/m3 TWA, respirable dust; (30)/(%Quartz + 3) mg/m3 TWA, total dust	0.1 mg/m3 TWA (respirable particulate)	0.025 mg/m3 TWA (respirable fraction)
Talc (14807-96-6)	TWAs	Not established	Not established	Not established	2 mg/m3 TWA (not containing fiber Asbestos, use NAB asbestos for talc containing fiber asbestos, respirable particulate)	4 mg/m3 TWA (airborne dust no otherwise classified); 2 mg/m3 TWA (particulate matter containing no Asbestos and <1% crystalline silica, respirable fraction)
Zinc powder, stabilized (7440-66-6)	Ceilings	Not established	0.4 mg/m3 Peak (respirable fraction); 4 mg/m3 Peak (inhalable fraction)	Not established	Not established	Not established
	MAKs	Not established	0.1 mg/m3 TWA MAK (respirable fraction); 2 mg/m3 TWA MAK (inhalable fraction)	Not established	Not established	Not established

Exposure Limits/Guidelines (Con't.)

	Result	Japan	Malaysia	Mexico	Netherlands	NIOSH
Asphalt (8052-42-4)	STELs	Not established	Not established	10 mg/m3 STEL [PPT-CT]	Not established	Not established
	TWAs	Not established	5 mg/m3 TWA (fume)	5 mg/m3 TWA VLE-PPT	Not established	Not established
	Ceilings	Not established	Not established	Not established	Not established	5 mg/m3 Ceiling (fume, 15 min)
Carbonic acid, magnesium salt (1:1) (546-93-0)	TWAs	Not established	10 mg/m3 TWA (particulate matter containing no Asbestos and <1% crystalline Silica)	Not established	Not established	10 mg/m3 TWA (total dust, listed under Magnesite); 5 mg/m3 TWA (respirable dust, listed under Magnesite)
Crystalline silica (14808-60-7)	TWAs	Not established	0.1 mg/m3 TWA (respirable fraction)	0.1 mg/m3 TWA VLE-PPT (respirable fraction)	0.075 mg/m3 TWA (respirable dust, listed under Silicon dioxide)	0.05 mg/m3 TWA (respirable dust)

Talc (14807-96-6)	TWAs	0.5 mg/m3 OEL (Class 1 Dust, respirable dust); 2 mg/m3 OEL (Class 1 Dust, total dust)	2 mg/m3 TWA (respirable fraction of particulate matter)	2 mg/m3 TWA VLE- PPT (respirable fraction)	0.25 mg/m3 TWA	2 mg/m3 TWA (containing no Asbestos and <1% Quartz, respirable dust)
Exposure Limits/Guidelines (Con't.)						
	Result	OSHA	OSHA Vacated	Portugal	Russia	Singapore
Asphalt (8052-42-4)	TWAs	Not established	Not established	0.5 mg/m3 TWA [VLE-MP] (fumes, inhalable fraction, as Benzene soluble aerosol)	Not established	5 mg/m3 PEL (fume)
Dolomite (16389-88-1)	TWAs	Not established	Not established	Not established	6 mg/m3 TWA (aerosol)	Not established
Crystalline silica (14808-60-7)	TWAs	50 µg/m3 TWA (listed under Respirable crystalline silica)	0.1 mg/m3 TWA (respirable dust)	0.025 mg/m3 TWA [VLE-MP] (respirable fraction)	1 mg/m3 TWA (glass, disintegration aerosol, total mass of aerosols, listed under Silicon dioxide amorphous and vitreous); 1 mg/m3 TWA (total mass of aerosols, listed under Crystalline silicon dioxide)	0.1 mg/m3 PEL (respirable dust)
	STELs	Not established	Not established	Not established	3 mg/m3 STEL (glass, disintegration aerosol, total mass of aerosols, listed under Silicon dioxide amorphous and vitreous); 3 mg/m3 STEL (regulated under Quartz, total mass of aerosols, listed under Silicon dioxide crystalline)	Not established
Talc (14807-96-6)	TWAs	Not established	2 mg/m3 TWA (<1% Crystalline silica, containing no Asbestos, respirable dust)	2 mg/m3 TWA [VLE- MP] (respirable fraction, particulate matter containing no Asbestos and <1% Crystalline silica)	Not established	2 mg/m3 PEL
Exposure Limits/Guidelines (Con't.)						
	Result	United Kingdom	United States - California	Venezuela		
Asphalt (8052-42-4)	TWAs	5 mg/m3 TWA (fumes)	5 mg/m3 PEL (fume)	0.5 mg/m3 TWA [VTRE-L-8/40 (fume, as Benzene soluble aerosols)		
	STELs	10 mg/m3 STEL (fumes)	Not established	Not established		
Crystalline silica (14808-60-7)	TWAs	Not established	0.3 mg/m3 PEL (total dust); 0.1 mg/m3 PEL (respirable dust)	0.025 mg/m3 TWA [VTRE-L- 8/40 (respirable fraction)		
Talc (14807-96-6)	TWAs	1 mg/m3 TWA (respirable dust)	2 mg/m3 PEL (respirable dust, containing no Asbestos fibers, <1% Crystalline silica)	2 mg/m3 TWA [VTRE-L-8/40 (respirable fraction; particulate containing no Asbestos and <1% Crystalline silica)		
	STELs	3 mg/m3 STEL (calculated, respirable dust)	Not established	Not established		

Exposure Control Notations

Mexico

- Asphalt (8052-42-4): **Carcinogens:** (A4 - Not classifiable as a human carcinogen)
- Talc (14807-96-6): **Carcinogens:** (A4 - Not classifiable as a human carcinogen)

Portugal

- Asphalt (8052-42-4): **Carcinogens:** (A4 - Not Classifiable as a Human Carcinogen (fumes))
- Crystalline silica (14808-60-7): **Carcinogens:** (A2 - Suspected Human Carcinogen)
- Talc (14807-96-6): **Carcinogens:** (A4 - Not Classifiable as a Human Carcinogen)

Indonesia

- Asphalt (8052-42-4): **Carcinogens:** (A4 - not classifiable as a human carcinogen)
- Talc (14807-96-6): **Carcinogens:** (A4 - not classifiable as a human carcinogen (not containing asbestos fiber))

Argentina

- Asphalt (8052-42-4): **Carcinogens:** (A4 - Not classifiable as a human carcinogen (fumes))
- Crystalline silica (14808-60-7): **Carcinogens:** (A2 - Suspected human carcinogen)
- Talc (14807-96-6): **Carcinogens:** (A1 - Confirmed human carcinogen)

Canada British Columbia

- Asphalt (8052-42-4): **Carcinogens:** (IARC Category 2A - Probable Human Carcinogen (fume; occupational exposure to oxidized Bitumens and their emissions during road paving); IARC Category 2B - Possible Human Carcinogen (fume; occupational exposure to straight-run Bitumens and their emissions during road paving)) | **Designated Substances:** (IARC Category 2B - Possible Human Carcinogen (fume; occupational exposure to straight-run Bitumens and their emissions during road paving); IARC Category 2A - Probable Human Carcinogen (fume; occupational exposure to oxidized Bitumens and their emissions during road paving))
- Crystalline silica (14808-60-7): **Carcinogens:** (ACGIH Category A2 - Suspected Human Carcinogen; IARC Category 1 - Human Carcinogen) | **Designated Substances:** (ACGIH Category A2 - Suspected Human Carcinogen; IARC Category 1 - Human Carcinogen)

Canada Manitoba

- Asphalt (8052-42-4): **Carcinogens:** (A4 Not Classifiable as a Human Carcinogen (fume, Coal tar-free))
- Crystalline silica (14808-60-7): **Carcinogens:** (A2 Suspected Human Carcinogen)
- Talc (14807-96-6): **Carcinogens:** (A4 Not Classifiable as a Human Carcinogen (containing no Asbestos fibers))

Canada New Brunswick

- Asphalt (8052-42-4): **Carcinogens:** (A4 - Not Classifiable as a Human Carcinogen (fumes))
- Talc (14807-96-6): **Carcinogens:** (A4 - Not Classifiable as a Human Carcinogen)

Canada Nova Scotia

- Asphalt (8052-42-4): **Carcinogens:** (A4 - Not Classifiable as a Human Carcinogen (fume, Coal tar-free))
- Crystalline silica (14808-60-7): **Carcinogens:** (A2 - Suspected Human Carcinogen)
- Talc (14807-96-6): **Carcinogens:** (A4 - Not Classifiable as a Human Carcinogen (containing no Asbestos fibers))

Canada Ontario

- Crystalline silica (14808-60-7): **Designated Substances:** (0.10 mg/m3 TWA (respirable fraction, listed under Silica, crystalline))

Canada Quebec

- Crystalline silica (14808-60-7): **Carcinogens:** (C2 carcinogen - effect suspected in humans)

Venezuela

- Asphalt (8052-42-4): **Ceilings:** (Present)
- Crystalline silica (14808-60-7): **Ceilings:** (Present)
- Talc (14807-96-6): **Ceilings:** (Present)

ACGIH

- Asphalt (8052-42-4): **Carcinogens:** (A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free))
- Crystalline silica (14808-60-7): **Carcinogens:** (A2 - Suspected Human Carcinogen)
- Talc (14807-96-6): **Carcinogens:** (A4 - Not Classifiable as a Human Carcinogen (containing no asbestos fibers))

Germany DFG

- Zinc powder, stabilized (7440-66-6): **Pregnancy:** (no risk to embryo/fetus if exposure limits adhered to (respirable; inhalable))
- Asphalt (8052-42-4): **Carcinogens:** (Category 2 (considered to be carcinogenic for man; aerosol and vapor)) | **Skin:** (skin notation (aerosol and vapour))
- Crystalline silica (14808-60-7): **Carcinogens:** (Category 1 (causes cancer in man; alveola fraction))
- Talc (14807-96-6): **Carcinogens:** (Category 3B (could be carcinogenic for man; free of asbestos fibers))

Exposure Limits Supplemental

Thailand

- Crystalline silica (14808-60-7): **Mineral Dusts:** (TWA ((250/(%SiO₂ + 5)), mppcf, respirable dust); TWA ((10/(%SiO₂ + 2)), mg/m³, respirable dust); TWA ((30/(%SiO₂ + 2)), mg/m³, total dust)
- Talc (14807-96-6): **Mineral Dusts:** (20 mppcf TWA)

Israel

- Asphalt (8052-42-4): **Biological Markers of Occupational Exposure:** (Medium: urine Time: end of shift at end of workweek Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative))

OSHA

- Crystalline silica (14808-60-7): **Mineral Dusts:** ((250)/(%SiO₂ + 5) mppcf TWA, respirable fraction; (10)/(%SiO₂ + 2) mg/m³ TWA, respirable fraction)
- Talc (14807-96-6): **Mineral Dusts:** (20 mppcf TWA (if 1% Quartz or more; use Quartz limit))

ACGIH

- Asphalt (8052-42-4): **BEIs:** (Medium: urine Time: end of shift at end of workweek Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)) | **TLV Basis - Critical Effects:** (eye and upper respiratory tract irritation (fume))
- Crystalline silica (14808-60-7): **TLV Basis - Critical Effects:** (lung cancer; pulmonary fibrosis)
- Talc (14807-96-6): **TLV Basis - Critical Effects:** (pulmonary fibrosis (containing no asbestos fibers); pulmonary function (containing no asbestos fibers))

8.2 Exposure controls

Engineering

- Good general ventilation should be used. Ventilation rates should be matched to conditions.

Measures/Controls

- If applicable, use process enclosures, local exhaust ventilation, or other engineering controls

to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal Protective Equipment

- Respiratory** • In case of insufficient ventilation, wear suitable respiratory equipment.
- Eye/Face** • Wear protective eyewear (goggles, face shield, or safety glasses).
- Skin/Body** • Rubber or cloth. Wear long sleeves and/or protective coveralls.
- Environmental Exposure Controls** • Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

BEI = Biological Exposure Indices

MAK = Maximale Arbeitsplatz Konzentration is the maximum permissible concentration

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

PEL = Permissible Exposure Level determined by the Occupational Safety and Health Administration (OSHA)

STEL = Short Term Exposure Limits are based on 15-minute exposures

TLV = Threshold Limit Value determined by the American Conference of Governmental Industrial Hygienists (ACGIH)

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

TWAEV = Time-Weighted Average Exposure Value

Section 9 - Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Material Description			
Physical Form	Solid	Appearance/Description	Light grey semi-solid paste with mild petroleum odor.
Color	Light grey.	Odor	Mild, petroleum.
Odor Threshold	Data lacking		
General Properties			
Boiling Point	> 260 °C(> 500 °F)	Melting Point/Freezing Point	Data lacking
Decomposition Temperature	Data lacking	pH	Data lacking
Specific Gravity/Relative Density	= 1.84 Water=1	Water Solubility	Data lacking
Viscosity	Data lacking	Explosive Properties	Data lacking
Oxidizing Properties:	Data lacking		
Volatility			
Vapor Pressure	Data lacking	Vapor Density	Data lacking
Evaporation Rate	Data lacking		
Flammability			
Flash Point	> 171 °C(> 339.8 °F)	UEL	Data lacking
LEL	Data lacking	Autoignition	Data lacking
Flammability (solid, gas)	Data lacking		
Environmental			
Octanol/Water Partition coefficient	Data lacking	Degradation	Data lacking

9.2 Other Information

- No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

- No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

- Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

10.4 Conditions to avoid

- Keep away from heat, sparks and flame.

10.5 Incompatible materials

- Strong oxidising agents.

10.6 Hazardous decomposition products

- Carbon monoxide, carbon dioxide, oxides of zinc.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Components		
Zinc powder, stabilized (50% TO 70%)	7440-66-6	Irritation: Skin-Human • 300 µg 3 Day(s)-Intermittent • Mild irritation; Tumorigen / Carcinogen: Ingestion/Oral-Mouse TDLo • 12.6 mg/kg 46 Week(s)-Continuous; <i>Tumorigenic:</i> Carcinogenic by RTECS criteria; Gastrointestinal:Tumors; Tumorigenic:Facilitates action of known carcinogen
Asphalt (0% TO 39.286%)	8052-42-4	Acute Toxicity: Ingestion/Oral-Rat LD50 • >5000 mg/kg; <i>Gastrointestinal:Hypermotility, diarrhea;</i> Inhalation-Rat LC50 • >94.4 mg/m ³ ; Multi-dose Toxicity: Inhalation-Rat TCLo • 100 mg/m ³ 6 Hour(s) 14 Week(s)-Intermittent; <i>Sense Organs and Special Senses:Olfaction:Tumors; Behavioral:Food intake (animal); Nutritional and Gross Metabolic:Gross Metabolite Changes:Weight loss or decreased weight gain;</i> Inhalation-Human TDLo • <10 mg/m ³ 5.5 Year(s)-Intermittent; <i>Sense Organs and Special Senses:Eye:Conjunctive irritation; Lungs, Thorax, or Respiration:Cough;</i> <i>Gastrointestinal:Changes in structure or function of salivary glands;</i> Mutagen: DNA adduct • Skin-Mouse • 600 mg/kg; Tumorigen / Carcinogen: Skin-Mouse TDLo • 130 g/kg 81 Week(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors; Skin and Appendages:Other:Tumors</i>
Crystalline silica (0.5% TO 40.036%)	14808-60-7	Acute Toxicity: Inhalation-Human TCLo • 16 mppcf 8 Hour(s) 17.9 Year(s)-Intermittent; <i>Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Lungs, Thorax, or Respiration:Cough;</i> <i>Lungs, Thorax, or Respiration:Dyspnea;</i> Inhalation-Rat TCLo • 200 mg/kg; <i>Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Lungs, Thorax, or Respiration:Other changes;</i> <i>Nutritional and Gross Metabolic:Changes in Chemistry or Temperature:Fe;</i> Multi-dose Toxicity: Inhalation-Hamster TCLo • 3 mg/m ³ 6 Hour(s) 78 Week(s)-Intermittent; <i>Lungs, Thorax, or Respiration:Fibrosis (interstitial); Lungs, Thorax, or Respiration:Changes in lung weight;</i> Inhalation-Rat TCLo • 58 mg/m ³ 13 Week(s)-Intermittent; <i>Lungs, Thorax, or Respiration:Other changes; Endocrine:Changes in thymus weight; Blood:Changes in leucocyte (WBC) count;</i> Inhalation-Rat TCLo • 80 mg/m ³ 26 Week(s)-Intermittent; <i>Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Blood:Changes in spleen; Immunological Including Allergic:Decrease in cellular immune response;</i> Mutagen: Micronucleus test • Unreported Route-Hamster • Lung (Somatic cell) • 160 µg/cm ³ ; DNA damage • Unreported Route-Human • Other Cell Type • 120 mg/L 24 Hour(s); Micronucleus test • Unreported Route-Human • Lung (Somatic cell) • 40 µg/cm ³ ; Tumorigen / Carcinogen: Inhalation-Rat TCLo • 50 mg/m ³ 6 Hour(s) 71 Week(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria; Liver:Tumors</i>
Zinc O,O-bis(mixed iso-butyl and pentyl) phosphorodithioate (0.5355% TO 0.714%)	68457-79-4	Acute Toxicity: Ingestion/Oral-Rat LD50 • 3.6 g/kg; <i>Behavioral:Somnolence (general depressed activity); Lungs, Thorax, or Respiration:Other changes; Gastrointestinal:Hypermotility, diarrhea</i>
Talc (3% TO 15%)	14807-96-6	Irritation: Skin-Human • 300 µg 3 Day(s)-Intermittent • Mild irritation; Tumorigen / Carcinogen: Inhalation-Rat • 11 mg/m ³ 1 Year(s)-Intermittent; <i>Tumorigenic:Equivocal tumorigenic agent by RTECS criteria; Lungs, Thorax, or Respiration:Tumors;</i> Inhalation-Rat TCLo • 18 mg/m ³ 6 Hour(s) 2 Year(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Bronchiogenic carcinoma; Endocrine:Tumors</i>
Dolomite (0.25% TO 1.5%)	16389-88-1	Reproductive: Ingestion/Oral-Rat TDLo • 15000 mg/kg (6-15D preg); <i>Reproductive Effects:Effects on Embryo or Fetus:Other effects on embryo</i>
Carbonic acid, magnesium salt (1:1) (0.05% TO 0.75%)	546-93-0	Acute Toxicity: Ingestion/Oral-Rat LD50 • 8000 mg/kg; Inhalation-Rat TCLo • 76 mg/m ³ 4 Hour(s); <i>Cardiac:Pulse rate increase without fall in BP; Liver:Liver function tests impaired; Kidney, Ureter, and Bladder:Other changes in urine composition</i>

GHS Properties	Classification
Acute toxicity	EU/CLP•Data lacking UN GHS 4•Data lacking OSHA HCS 2012•Data lacking WHMIS 2015•Data lacking
Skin corrosion/Irritation	EU/CLP•Data lacking UN GHS 4•Skin Mild Irritation 3 OSHA HCS 2012•Data lacking WHMIS 2015•Data lacking
Serious eye damage/Irritation	EU/CLP•Data lacking UN GHS 4•Data lacking OSHA HCS 2012•Data lacking WHMIS 2015•Data lacking
Skin sensitization	EU/CLP•Data lacking UN GHS 4•Data lacking OSHA HCS 2012•Data lacking WHMIS 2015•Data lacking
Respiratory sensitization	EU/CLP•Data lacking UN GHS 4•Data lacking OSHA HCS 2012•Data lacking WHMIS 2015•Data lacking
Aspiration Hazard	EU/CLP•Data lacking UN GHS 4•Data lacking OSHA HCS 2012•Data lacking WHMIS 2015•Data lacking
Carcinogenicity	EU/CLP•Carcinogenicity 2; Suspected of causing cancer UN GHS 4•Carcinogenicity 2 OSHA HCS 2012•Carcinogenicity 2 WHMIS 2015•Carcinogenicity 2
Germ Cell Mutagenicity	EU/CLP•Data lacking UN GHS 4•Data lacking OSHA HCS 2012•Data lacking WHMIS 2015•Data lacking
Toxicity for Reproduction	EU/CLP•Data lacking UN GHS 4•Data lacking OSHA HCS 2012•Data lacking WHMIS 2015•Data lacking
STOT-SE	EU/CLP•Data lacking UN GHS 4•Data lacking OSHA HCS 2012•Data lacking WHMIS 2015•Data lacking
STOT-RE	EU/CLP•Data lacking UN GHS 4•Data lacking OSHA HCS 2012•Data lacking WHMIS 2015•Data lacking

Potential Health Effects

Inhalation

Acute (Immediate) • Under normal conditions of use, no health effects are expected.

Chronic (Delayed) • No data available

Skin

Acute (Immediate) • Causes mild skin irritation.

Chronic (Delayed) • No data available

Eye

Acute (Immediate) • Under normal conditions of use, no health effects are expected.

Chronic (Delayed) • No data available

Ingestion

Acute (Immediate) • Under normal conditions of use, no health effects are expected.

Chronic (Delayed) • No data available

Carcinogenic Effects • Repeated and prolonged exposure may cause cancer.

Carcinogenic Effects			
	CAS	IARC	NTP
Asphalt	8052-42-4	Group 2B-Possible Carcinogen	Not Listed
Crystalline silica	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen

Key to abbreviations

LC = Lethal Concentration

LD = Lethal Dose

TC = Toxic Concentration

TD = Toxic Dose

Section 12 - Ecological Information

12.1 Toxicity

Components		
Zinc powder, stabilized (50% TO 70%)	7440-66-6	<p>Aquatic Toxicity-Fish: 96 Hour(s) LC50 <i>Pimephales promelas (Fathead Minnow)</i> 0.238 mg/L Comments: Trace Metals Toxicity and Bioaccumulation in Mudskipper <i>Periophthalmus waltoni</i> Koumans 1941 (Gobiidae: Perciformes)</p> <p>28 Day(s) NOEC <i>Cyprinus carpio (Common Carp)</i> 0.0026 mg/L Comments: Bioaccumulation of Micropollutants and Biomarker Responses in Caged Carp (<i>Cyprinus carpio</i>)</p> <p>Aquatic Toxicity-Crustacea: 21 Day(s) NOEC Water Flea 0.062 mg/L Comments: Bioavailability Models for Predicting Acute and Chronic Toxicity of Zinc to Algae, Daphnids, and Fish in Natural Surface Waters</p> <p>48 Hour(s) EC50 <i>Ceriodaphnia dubia</i> 0.07 mg/L Comments: Influence of Water Chemistry on the Acute Toxicity of Copper and Zinc to the Cladoceran <i>Ceriodaphnia cf dubia</i></p> <p>Aquatic Toxicity-Algae and Other Aquatic Plant(s): 72 Hour(s) EC50 <i>Pseudokirchneriella subcapitata (Green Algae)</i> 0.106 mg/L Comments: Bioavailability Models for Predicting Acute and Chronic Toxicity of Zinc to Algae, Daphnids, and Fish in Natural Surface Waters</p> <p>14 Day(s) NOEC <i>Euglena gracilis (Flagellate Euglenoid)</i> 0.0075 mg/L Comments: Water Quality Bioassay Using Selected Protozoa, II. The Effects of Zinc on Population Growth of <i>Euglena gracilis</i></p>

• Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

• Material data lacking.

12.3 Bioaccumulative potential

• Material data lacking.

12.4 Mobility in Soil

• Material data lacking.

12.5 Results of PBT and vPvB assessment

• No PBT and vPvB assessment has been conducted.

12.6 Other adverse effects

• No studies have been found.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste • Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste • Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN3077	Environmentally hazardous substance, solid, n.o.s. (65% Zinc)	9	III	NDA
TDG	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (65% Zinc)	9	III	NDA
IMO/IMDG	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (65% Zinc)	9	III	NDA
IATA/ICAO	UN3077	Environmentally hazardous substance, solid, n.o.s. (65% Zinc)	9	III	NDA

14.6 Special precautions for user

• None specified.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code • Data lacking.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications

• Acute

State Right To Know		
Component	CAS	PA
Asphalt	8052-42-4	Yes
Carbonic acid, magnesium salt (1:1)	546-93-0	No
Chlorite	1318-59-8	No
Crystalline silica	14808-60-7	Yes
Dolomite	16389-88-1	No
Talc	14807-96-6	Yes
Zinc O,O-bis(mixed iso-butyl and pentyl) phosphorodithioate	68457-79-4	No
Zinc powder, stabilized	7440-66-6	Yes

Inventory						
Component	CAS	Australia AICS	Canada DSL	Canada NDSL	China	EU EINECS
Asphalt	8052-42-4	Yes	Yes	No	Yes	Yes
Carbonic acid, magnesium salt (1:1)	546-93-0	Yes	Yes	No	Yes	Yes
Chlorite	1318-59-8	No	No	No	Yes	Yes
Crystalline silica	14808-60-7	Yes	Yes	No	Yes	Yes
Dolomite	16389-88-1	Yes	No	Yes	Yes	Yes
Talc	14807-96-6	Yes	Yes	No	Yes	Yes
Zinc O,O-bis(mixed iso-butyl	68457-79-4	Yes	Yes	No	Yes	Yes

and pentyl) phosphorodithioate						
Zinc powder, stabilized	7440-66-6	Yes	Yes	No	Yes	Yes
Inventory (Con't.)						
Component	CAS	EU ELNICS	Japan ENCS	TSCA		
Asphalt	8052-42-4	No	No	Yes		
Carbonic acid, magnesium salt (1:1)	546-93-0	No	Yes	Yes		
Chlorite	1318-59-8	No	No	No		
Crystalline silica	14808-60-7	No	Yes	Yes		
Dolomite	16389-88-1	No	No	Yes		
Talc	14807-96-6	No	Yes	Yes		
Zinc O,O-bis(mixed iso-butyl and pentyl) phosphorodithioate	68457-79-4	No	Yes	Yes		
Zinc powder, stabilized	7440-66-6	No	No	Yes		

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

•Chlorite	1318-59-8	Not Listed
•Dolomite	16389-88-1	Not Listed
•Talc	14807-96-6	Not Listed
•Asphalt	8052-42-4	Not Listed
•Carbonic acid, magnesium salt (1:1)	546-93-0	Not Listed
•Zinc powder, stabilized	7440-66-6	Not Listed
•Zinc O,O-bis(mixed iso-butyl and pentyl) phosphorodithioate	68457-79-4	Not Listed
•Crystalline silica	14808-60-7	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

•Chlorite	1318-59-8	Not Listed
•Dolomite	16389-88-1	Not Listed
•Talc	14807-96-6	Not Listed
•Asphalt	8052-42-4	Not Listed
•Carbonic acid, magnesium salt (1:1)	546-93-0	Not Listed
•Zinc powder, stabilized	7440-66-6	Not Listed
•Zinc O,O-bis(mixed iso-butyl and pentyl) phosphorodithioate	68457-79-4	Not Listed
•Crystalline silica	14808-60-7	Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

•Chlorite	1318-59-8	Not Listed
•Dolomite	16389-88-1	Not Listed
•Talc	14807-96-6	Not Listed
•Asphalt	8052-42-4	Not Listed
•Carbonic acid, magnesium salt (1:1)	546-93-0	Not Listed
•Zinc powder, stabilized	7440-66-6	Not Listed
•Zinc O,O-bis(mixed iso-butyl and pentyl) phosphorodithioate	68457-79-4	Not Listed
•Crystalline silica	14808-60-7	Not Listed

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

•Chlorite	1318-59-8	Not Listed
•Dolomite	16389-88-1	Not Listed
•Talc	14807-96-6	Not Listed
•Asphalt	8052-42-4	Not Listed
•Carbonic acid, magnesium salt (1:1)	546-93-0	Not Listed
•Zinc powder, stabilized	7440-66-6	Not Listed
•Zinc O,O-bis(mixed iso-butyl and pentyl) phosphorodithioate	68457-79-4	Not Listed
•Crystalline silica	14808-60-7	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

•Chlorite	1318-59-8	Not Listed
•Dolomite	16389-88-1	Not Listed
•Talc	14807-96-6	Not Listed
•Asphalt	8052-42-4	Not Listed

•Carbonic acid, magnesium salt (1:1)	546-93-0	Not Listed
•Zinc powder, stabilized	7440-66-6	Not Listed
•Zinc O,O-bis(mixed iso-butyl and pentyl) phosphorodithioate	68457-79-4	Not Listed
•Crystalline silica	14808-60-7	Not Listed
U.S. - California - Proposition 65 - Reproductive Toxicity - Male		
•Chlorite	1318-59-8	Not Listed
•Dolomite	16389-88-1	Not Listed
•Talc	14807-96-6	Not Listed
•Asphalt	8052-42-4	Not Listed
•Carbonic acid, magnesium salt (1:1)	546-93-0	Not Listed
•Zinc powder, stabilized	7440-66-6	Not Listed
•Zinc O,O-bis(mixed iso-butyl and pentyl) phosphorodithioate	68457-79-4	Not Listed
•Crystalline silica	14808-60-7	Not Listed

15.2 Chemical Safety Assessment

- No Chemical Safety Assessment has been carried out.

Section 16 - Other Information

Relevant Phrases (code & full text)

- H350i - May cause cancer by inhalation.
- H372 - Causes damage to organs through prolonged or repeated exposure.

Revision Date

- 10/July/2017

Last Revision Date

- 10/July/2017

Preparation Date

- 10/July/2017

Disclaimer/Statement of Liability

- The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key to abbreviations

NDA = No Data Available