

Tuf-Lon



Tuf-Lon is an industrial thread compound that is blended using a premium based hydrocarbon grease as the carrier. Tuf-Lon contains a high concentration of polyethylene particles which fill in the helix of the connection and provide maximum sealing under pressure.

The product has been certified by an independent engineering firm to seal gas connections above 10,000 psi (68.9 MPa).

▶ SERVICE RECOMMENDATIONS

Tuf-Lon is an extreme pressure sealant that is recommended for high pressure gas lines as well as commercial and residential water lines.

▶ PERFORMANCE CHARACTERISTICS

- Smooth black grease containing polyethylene particles
- Easy to apply by brush to threaded connections
- Long storage shelf life

▶ PRODUCT SPECIFICATIONS

Thickener	Calcium Sulfonate Complex
Fluid Type	Petroleum
Flash Point	> 180°C / 356°F
Service Rating	220°C / 428°F
NLGI Grade	1
Color	Black
Pen Range	300 – 360 (ASTM D217) seasonal adjustment
Brushability	-18°C / 0°F
Drop Point	> 204°C / 400°F

▶ PACKAGING

225 ml Brush Top Can	Net 227 gm / 1/2 lb
500 ml Brush Top Can	Net 454 gm / 1lb
4.5 l steel / 1.0 gallon	Net 907 gm / 2 lb

Warranty: This compound shall be free of defects at time of manufacture. Warranty shall be limited to the refund of the purchase price. All other liability is negated and disclaimed and Topco Oilsite Products shall not be liable for consequential or incidental damages.



www.topcooilsite.com

toll free: 1-800-222-6448

