



# GREEN SEAL II THERMAL



Green-Seal II Thermal is a premium thermal compound formulated for use on casing and tubing used in high temperature steam injection services.

This environmentally friendly product is free of all heavy metals. It is blended using synthetic base materials and has a proprietary loading of inorganic additives to protect against extreme wear. Anti-corrosion inhibitors ensure that tubulars may be stored for extended periods of time without concern for pitting of the threads.

The premium quality greases allow for ease of application of Green Seal II Thermal in all types of weather conditions.

Green Seal II Thermal has a coefficient of friction that is similar to that of API Modified. This characteristic allows the compound to be run at standard pipe torques as recommended by the manufacturer.

## Product Specifications

Service Rating	371°C / 700°F
Drop Point	386°C / 727° F
Brushability	-18 °C / 0° F

## Service Recommendations

API casing, tubing, and premium threaded connections

## Packaging

10 L Metal	Net 13.6 kg	Net 30 lb
20 L Metal	Net 22.7 kg	Net 50 lb

Refer to Manufacturer's Material Safety Data Sheet for Precautionary and Handling Information

**LOCATIONS**

**Calgary Office**  
 Bay 7, 3401 - 19 Street N.E.  
 Calgary, AB T2E 6S8  
 Phone: 403/219-0255  
 Fax: 403/291-3042

**Clairmont Office**  
 9402 - 99 Street  
 Clairmont, AB T0H 0W0  
 Phone: 780/567-2398  
 Fax: 780/567-2413

**Red Deer Distribution Centre**  
 7932 Edgar Industrial Way  
 Red Deer, AB T4P 3R2  
 Phone: 403/341-4417  
 Fax: 403/346-5122

**Redcliff Office**  
 114 Elbow Drive N.E.  
 Redcliff, AB T0J 2P0  
 Phone: 403/526-3321  
 Fax: 403/526-8036

**Edmonton Distribution Centre**  
 9519 - 28 Avenue  
 Edmonton, AB T6N 0A3  
 Phone: 780/436-3400  
 Fax: 780/436-3659

**Oklahoma City Distribution Centre**  
 8200 West Reno  
 Oklahoma City, OK  
 USA 73127  
 Phone: 405/491-8521  
 Fax: 405/491-8521

**TOLL FREE: 1-800-222-6449**



**www.topcoilsite.com**