





## **SPECIFICATIONS**

HOISTING CAPACITY

**TOPHEAD** 

**TOPHEAD TRAVEL** 

**PLUMBING** 

**ENGINES** 

**DRILLER'S CABIN** 

300,000 lbs hookload capacity for full hookload capacity from table to crown.

Two (2) speeds rated at 0-60 RPM up to 23,000 ft/lbs torque. 0-120 RPM up to 11,500 ft/lbs torque. Rotary brake for directional drilling.

Adequate working space for Range III drill pipe and casing. Tophead hoist speed 109 ft/min. Tophead travel down speed 133 ft/min. Tophead equipped to handle elevators and links.

Rig is hard-piped with 5,000 PSI rating for mud or air plumbing, complete with remote control actuated valves.

1100 HP from twin CAT C-18 engines.

Designed for horizontal and vertical drilling with all functions digitally monitored from driller's cabin.

High-tech driller's cabin is explosion proof and climate controlled. Two (2) remotely controlled cameras allow driller to monitor drilling functions. One (1) umbilical cord controls all actions from cabin.

Minimal labor required. Driller can perform much of the set-up alone with remote controls. The floor hand with spinner allows safe pipe make-up and break-out.

Drill is designed to lay mast over with casing or drill pipe in the table for easy and safe service.

## **SUMMARY**

Although this unit is specially designed for drilling in a confined space, it is a great package for multiple applications.

All electric over hydraulic controls for safe operation with minimal labor requirements.

All functions and digital video from two (2) remote controlled cameras can be monitored by the internet from anywhere in the world.

Excellent for horizontal and vertical drilling.

